

Printing date 02/21/2018 Reviewed on 02/21/2018

1 Identification

- · Product identifier

 - Trade name: EP1310 Clear A
 Recommended use Epoxy Resin
 Restrictions on use For industrial use only
- · Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Manufacturer/Supplier.
ResinLab, LLC
N109 W13300 Ellsworth Drive
Germantown, WI 53022
1-877-259-1669
www.resinlab.com
Information Department: Product Safety Department: msds@resinlab.com
Emarcancy Telephone Number:

Emergency Telephone Number: North America - Chemtrec: 1-800-424-9300 (24 hours) International - Chemtrec: 01-703-527-3887 (24 hours)

2 Hazard(s) identification

· Classification of the substance or mixture

H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT RE 2 H373 May cause damage to the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Oral.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07

GHS08

· Signal word Warning

· Hazard-determining components of labeling: Bisphenol-A-(epichlorohydrin) epoxy resin

Benzophenone 1,1,1-trimethylolpropane triacrylate

Hazard statements

Hazard statements
H319 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H373 May cause damage to the kidneys and the liver through prolonged or repeated exposure. Route of exposure: Oral.
Precautionary statements
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves / eye protection / face protection.
If on skin: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Get medical advice/attention if you feel unwell.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.
Collect spillage.

Collect spillage.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system: NFPA System · NFPA ratings (scale 0 - 4)



Health = 2Fire = 1Reactivity = 0

NFPA special hazards (water reactivity and oxidizing property): None

HMIS System HMIS-ratings (scale 0 - 4)



Health = *2Fire = 1 Reactivity = 0

Other hazards

Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.





Printing date 02/21/2018 Reviewed on 02/21/2018

Trade name: EP1310 Clear A

(Contd. of page 1)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Dangerous components:		
CAS: 25068-38-6 NLP: 500-033-5	Bisphenol-A-(epichlorohydrin) epoxy resin Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	50-60%
CAS: 15625-89-5		20-30%
EINECS: 239-701-3 Index number: 607-111-00-9 RTECS: AT 4810000	1,1,1-trimethylolpropane triacrylate Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	20-30%
CAS: 119-61-9 EINECS: 204-337-6 RTECS: DI 9950000	Benzophenone STOT RE 2, H373 Aquatic Chronic 2, H411 Aquatic Acute 2, H401	≥1-<2.5%

Additional information:
If the chemical name/CAS number is proprietary and or weight percentage is listed as a range, the specific chemical identity and or percentage of composition has been withheld as a trade secret.

4 First-aid measures

· Description of first aid measures

General information: Keep warm, position comfortably and cover well.

· After inhalation:

Remove victim from exposure to fresh air. Keep person at rest. Provide oxygen if person is not breathing. Supply fresh air and if symptoms occur call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Remove all contaminated clothing and wash before reuse.

If skin rash or irritation occurs, seek medical advice.

After eye contact:

Immediately flush opened eyes with water for 5 minutes, then remove contact lenses if present, continue flushing for at least another 15 Immediately flush opened eyes with water for a minutes.

If symptoms develop seek medical attention.

After swallowing:

If victim is unconscious; never give anything by mouth.

If victim is conscious, rinse out mouth with water.

Get medical attention if you feel unwell.

Information for doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available. Indication of any immediate medical attention and special treatment needed Check section 11 Toxicological Information for further relevant information.

5 Fire-fighting measures

Extinguishing media
 Suitable extinguishing agents:
 Use fire fighting measures that suit the environment.
 Alcohol resistant foam
 dry chemical
 Crystelicidae.

Carbon dioxide
Fire-extinguishing powder

Special hazards arising from the substance or mixture
Will not burn unless preheated.
In case of fire, the following can be released:
Phanolics

Phenolics

Carbon dioxide (CO₂) and Carbon monoxide (CO) **Advice for firefighters**

Protective equipment:

Mouth respiratory protective device.

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA fire brigades standard (29 CFR 1910.156).

As with any fire, wear positive-pressure self-contained breathing apparatus and full protective gear that are NIOSH approved.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective clothing. Mount respiratory protective device.

Do not breathe gas, vapors, dusts or mists if their inhalable particles occur during use.

Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up:

For large spills: provide diking or containment to minimize spreading. If possible pump and store material in appropriate container.

For small spills: Ventilate and wash area. Collect spills and absorbant material in appropriate container.

Ensure adequate ventilation.

Allow molten product to cool.

Allow molten product to cool.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)





Printing date 02/21/2018 Reviewed on 02/21/2018

Trade name: EP1310 Clear A

Dispose contaminated material as waste according to item 13.

(Contd. of page 2)

7 Handling and storage

Handling:
Precautions for safe handling

Avoid breathing vapor or spray mists. Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

Keep away from incompatible material(s). Avoid any release into the environment. Do not breathe dust/fumes/mist/vapor/spray.

Avoid contact with eyes, skin and clothing. Keep away from heat,sparks, flames and ignition sources. Observe all the personal protection requirements in Section 8.

· Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Provide ventilation for receptacles.

Keep stored in accordance with local, regional, national, and international regulations.

8 Exposure controls/personal protection

Control parameters

Components with limit values that require monitoring at the workplace:

15625-89-5 1,1,1-trimethylolpropane triacrylate

WEEL Long-term value: 1 mg/m3

Skiň

119-61-9 Benzophenone

WEEL Long-term value: 0.5 mg/m3

· Additional Occupational Exposure Limit Values for possible hazards during processing: None.

Exposure controls

If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment:

General protective and hygienic measures:
Be sure to clean skin thoroughly after work and before breaks.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Avoid contact with the eyes and skin.

Personal Protective Equipment (PPE)

Breathing equipment:
Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended

Use a NIOSH approved air-purifying organic vapor respirator if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air supplied respirator. Observe OSHA regulations (29CFR 1910.134) for respirator use.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves



Chemical resistant gloves

· Eye protection:



Safety Glasses with side shields

Body protection: Appropriate chemical resistant clothing.
 Limitation and supervision of exposure into the environment
 The Engineering measures or controls, and PPE recommendations are only guidelines and may not apply to every situation. For additional information, please consult the corresponding requirements under OSHA 29 CFR 1910.94-95, and 29 CFR 1910.132-138.

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance: Form:

Liquid



Printing date 02/21/2018 Reviewed on 02/21/2018

Trade name: EP1310 Clear A

		(Contd. of page 3
· Color: · Odor: · Odor threshold:	Clear Mild epoxy odor Not determined.	
· pH-value:	Not determined.	
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. >200 °C (>392 °F)	
· Flash point:	>110 °C (>230 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	Not determined.	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits: Lower: Upper:	Not determined. Not determined.	
· Vapor pressure: · Vapor Density:	Not determined. not determined	
Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate	1.14 g/cm³ (9.51 lbs/gal) Not determined. Not determined. Not determined.	
Solubility in / Miscibility with Water: organic solvents:	Not miscible or difficult to mix. Miscible with many organic solvents.	
· Partition coefficient (n-octanol/wate	er): Not determined.	
Viscosity:	Not available. Not available.	

10 Stability and reactivity

- Reactivity Not a regulated physical hazard under GHS.
- Hazardous Reactivity and Chemical Stability Stable under normal conditions of use, storage and temperatures.

 Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.

 Possibility of hazardous reactions In contact with incompatible materials.

 Conditions to avoid Keep away from heat, sparks, flame and any other ignition sources.

- Incompatible materials:

inert gases, free radical initiators, oxygen scavengers. Oxidizing agents Mercaptans

Acids Reducing agents

- Amines
 Bases (Alkalis)
 Hazardous decomposition products: Possible in traces.
- Additional information:
- As long as the prescribed application concentrations are maintained there is no danger that stable emulsions will form.

11 Toxicological information · Information on toxicological effects Acute toxicity: LD/LC50 values that are relevant for classification: 25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin LD50 11,400 mg/kg (rat) Oral Dermal LD50 20,000 mg/kg (rabbit) (Test guideline not available) Inhalative LC50/4 h mg/l (Test species: n/a) (Toxicity not expected based on the acute oral data) 15625-89-5 1,1,1-trimethylolpropane triacrylate 5,700 mg/kg (rat) (Calculated from 5.19 mL/kg) Reference: ChemID Full Record (2011). Oral LD50 2,500 mg/kg (mouse) Reference: HSNO CCID (2011). Dermal LD50 Inhalative LC50/4 h mg/l (Test species: n/a) (None or low toxicity based on the acute oral data) 25036-25-3 Polymer of Epoxy resin and Bisphenol-A >2,000 mg/kg (rat) >2,000 mg/kg (rat) Reference: ChemID (2010) and Dow (M)SDS (2003). LD50 >2,000 mg/kg (read across from 101-68-8) Reference: NLM Toxnet (2010) LD50 Dermal

(Contd. on page 5



Printing date 02/21/2018 Reviewed on 02/21/2018

Trade name: EP1310 Clear A

			(Contd. of page 4)
Inhalative	LC50/4 h	mg/l (Test species: n/a) (Toxicity not expected based on the acute oral data)	(,
947-19-3 F	Hydroxycy	yclohexylphenylketone	
Oral	LD50	2,895 mg/kg (rat) 2500 - 5000 mg/kg (rat) (OECD TG 423) Reference: HSNO CCID (2011) and ECHA (2011).	
		mg/kg (rat) (LD0≥5000 mg/kg; OECD TG 402) No death reported at 5000 mg/kg; the substance was not an acute dermal hazard. Reference: ECHA (2011).	
Inhalative	LC50/4 h	mg/l (rat) (OECD TG 403; inhalation: aerosol) No death occurred when inhalation with 1000 mg/m³ of the aerosolized substance for 4 hours. Reference: ECHA (2011).	
119-61-9 E	Benzophe	none	
Oral	LD50	2,895 mg/kg (mouse)	
Dermal	LD50	3,535 mg/kg (rabbit) (no test detail available) Reference: ECHA (2011).	
Inhalative	LC50/4 h	mg/l (Test species: n/a) (Toxicity not expected due to wetted form)	
D.	imanus iuuis	tant officet:	

Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.
 • on the eye: Irritating effect.
 • Sensitization: Sensitization possible through skin contact.
 Additional toxicological information:
 The product shows the following dangers according to internally approved calculation methods for preparations: Irritory

Carcinogenic categories

IARC (International Agency for Research on Cancer)

119-61-9 Benzophenone

2B

NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

•	Toxicity

Aquatic toxicity:

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

EC50 mg/kg (rabbit)

15625-89-5 1,1,1-trimethylolpropane triacrylate

EC50 mg/kg (rabbit) (Skin irritation: 5/8 (Max. 8))
Skin irritation: 5/8 (Max. 8; mean score of all treated animals).
The substance was classified as irritating to rabbit skin (Category 2) based on the classification criteria.
Reference: Cognis (M)SDS (2007) and IUCLID Dataset (2000).

25036-25-3 Polymer of Epoxy resin and Bisphenol-A

EC50 mg/kg (No data available)

947-19-3 Hydroxycyclohexylphenylketone

EC50 mg/kg (rabbit) (EPA OPP 81-5; occlusive; 24hr-contact)
Overall irritation: 1.3/4 (Max. 4; Intact skin; Time-point: 24 hrs; mean score of all treated animals)
Overall irritation: 0./4 (Max. 4; Intact skin; Time-point: 72 hrs - 7days; mean score of all treated animals)
Overall irritation: 0.7/4 (Max. 4; Abraded skin; Time-point: 24 hrs; mean score of all treated animals)
Overall irritation: 0.2/4 (Max. 4; Abraded skin; Time-point: 7 days; mean score of all treated animals)
From view point of safety, the substance was classified as a slight skin irritant (Category 3).
Reference: ECHA (2011).

119-61-9 Benzophenone

EC50 mg/kg (rabbit) (Draize method)
Primary dermal irritation index (PDII): 2.0 (mean score of all treated animals): slight erythema and edema exhibited.
not irritating (rabbit) (OECD TG 404; No sighs of irritation observed)
Overall irritation: 0 (Time-point: 24+48+72 hrs; mean score of all treated animals): No sighs of irritation observed in the treated animalş

For safety reason, the substance was classified as a slight irritant (Category 3) to rabbit skin. Reference: ECHA (2011).

· Persistence and degradability No further relevant information available.

Other information: The product is easily biodegradable. Behavior in environmental systems:

Bioaccumulative potential No data available.

Mobility in soil No further relevant information available.

Additional ecological information: The product is non-rapid degradable, and low or not highly bioaccumulative.

General notes:

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment

PBT: None of the ingredients is listed.

vPvB: None of the ingredients is listed.

Other adverse effects No further relevant information available.



Reviewed on 02/21/2018 Printing date 02/21/2018

Trade name: EP1310 Clear A

(Contd. of page 5)

13 Disposal considerations

Waste treatment methods
 Recommendation:
 Must be specially treated adhering to official regulations.
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings: Recommendation: Dispose of according to your local waste regulations.

4 Transport information	
· UN-Number · DOT, IMDG, IATA	UN3082
· UN proper shipping name · DOT	Enyironmentally hazardous substances, liquid, n.o.s. (Bisphen
· IMDG	Environmentally hazardous substances, liquid, n.o.s. (Bisphen A-(epichlorohydrin) epoxy resin, trimethylolpropane triacrylate) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUI N.O.S. (Bisphenol-A-(epichlorohydrin) epoxy resi trimethylolpropane triacrylate), MARINE POLLUTANT
· IATA	trimetriyiopropane triacrylate), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUI N.O.S. (Bisphenol-A-(epichlorohydrin) epoxy resi trimethylolpropane triacrylate)
· Transport hazard class(es)	
DOT, IMDG, IATA	
· Class · Label	9 Miscellaneous dangerous substances and articles 9
Packing group DOT, IMDG, IATA	III
· Environmental hazards:	Not applicable.
Special precautions for user Danger code (Kemler): EMS Number: Stowage Category	Warning: Miscellaneous dangerous substances and articles 90 F-A,S-F A
· Transport in bulk according to Annex II of MARPO IBC Code	DL73/78 and the Not applicable.
· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: No limit On cargo aircraft only: No limit
· Remarks:	Special marking with the symbol (fish and tree).
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (BISPHENOL-A-(EPICHLOROHYDRIN) EPOX RESIN, TRIMETHYLOLPROPANE TRIACRYLATE), 9, III

15 Regulatory information	
· Safety, health and environmental regulations/legislation specific for the substance or mixt	ture
· SARA Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· SARA Section 313 (Specific toxic chemical listings):	
None of the ingredients is listed.	
· SARA Section 311/312 (Hazardous Chemical Inventory Reporting)	
25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin	A, C 50-60%
15625-89-5 1,1,1-trimethylolpropane triacrylate	A, R 20-30%
25036-25-3 Polymer of Epoxy resin and Bisphenol-A	C ≥5-<10%
119-61-9 Benzophenone	A, C ≥1-<2.59

· Hazard Abbreviations for SARA 311/312



Printing date 02/21/2018 Reviewed on 02/21/2018

Trade name: EP1310 Clear A

(Contd. of page 6)

A - Acute Health Hazard C - Chronic Health Hazard F - Fire Hazard

R - Reactive Hazard

S - Sudden Release of Pressure Hazard

TSCA (Toxic Substances Control Act):

All ingredients are listed.

Proposition 65

Chemicals known to cause cancer:
This product contains a chemical known in the State of California to cause cancer.

119-61-9 Benzophenone

122-60-1 Phenyl glycidyl ether

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

80-05-7 Bisphenol A

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· International Regulation Lists

· Chinese Chemical Inventory of Existing Chemical Substances:

All ingredients are listed.

· GHS label elements GHS label elements

· National regulations:

Japanese Existing and New Chemical Substance List:

All ingredients are listed.

Korean Existing Chemical Inventory:

All ingredients are listed.

European Pre-registered substances:

All ingredients are listed.

· EINECS List:

15625-89-5 1,1,1-trimethylolpropane triacrylate

947-19-3 Hydroxycyclohexylphenylketone

119-61-9 Benzophenone

· ELINCS List:

None of the ingredients is listed.

REACh - Substances of Very High Concern (SVHC) List:

None of the ingredients is listed.

Restriction of Hazardous Substances Directive (RoHS) list:

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Department Issuing (M)SDS: Product Development Department
 Contact: msds@resinlab.com
 Date of preparation / last revision 02/21/2018 / 2
 * Data compared to the previous version altered.