

Safety Data Sheet
acc. to OSHA HCS

Print Date 05/19/2015

Revision Date 05/19/2015

Product Identifier

- Trade Name: **EP1305LV Black A**
- Application of the Substance or Mixture: *Epoxy Resin*

Details of the Supplier of the Safety Data Sheet (SDS)

- Manufacturer or Supplier:**
Resinlab, LLC
N109 W13300 Ellsworth Drive,
Germantown, WI 53022
1-800-388-8605
www.resinlab.com
- Information Department:** Product Safety Department: msds@resinlab.com
- Emergency Telephone Number:**
North America - Chemtrec: 1-800-424-9300 (24 hours)
International - Chemtrec: 01-703-527-3887 (24 hours)

2 Hazard(s) identification

Hazard Classification



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Label Elements

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Pictogram(s)



GHS07 GHS09

Signal Word *Warning*

Hazard-determining Component(s)

Bisphenol-A-(epichlorohydrin) epoxy resin
1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Hazard statements

Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves.
Wear eye protection / face protection.
Avoid release to the environment.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
If skin irritation or rash occurs: Get medical advice/attention.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/19/2015

Revision Date 05/19/2015

Trade Name: EP1305LV Black A

(Contd. of page 1)

If eye irritation persists: Get medical advice/attention.
 If on skin: Wash with plenty of water.
 Collect spillage.
 Take off contaminated clothing and wash it before reuse.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
 Wear protective gloves/protective clothing/eye protection/face protection.
 Avoid release to the environment.
 Wash thoroughly after handling.
 Contaminated work clothing must not be allowed out of the workplace.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard Rating System
NFPA System
NFPA Ratings (scale 0 - 4)


NFPA special hazards (water reactivity and oxidizing property): None

HMIS System
HMIS Ratings (scale 0 - 4)

HEALTH	2	Health = 2
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0





Other hazards
Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3 Composition/information on ingredients

Chemical Characterization: Mixtures
Composition/Information on Ingredients

CAS: 25068-38-6 NLP: 500-033-5 Index Number: 603-074-00-8	Bisphenol-A-(epichlorohydrin) epoxy resin  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	70-80%
CAS: 74398-71-3 EC number: 616-085-8	1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335 Aquatic Acute 2, H401	10-20%
CAS: 1333-86-4 EINECS: 215-609-9 RTECS: FF5800000	Carbon black	0.1-<1%

Classification System:

The Classifications were based on the Toxicological and Ecological Data of the substances/mixtures in the Section 11 and 12.

US

(Contd. on page 3)

Safety Data Sheet acc. to OSHA HCS

Print Date 05/19/2015

Revision Date 05/19/2015

Trade Name: EP1305LV Black A

(Contd. of page 2)

4 First-aid measures

Description of First Aid Measures

General Information

Ensure medical personnel are aware of exposure and take precautions for their personal protection; see Section 8 for the information of personal protection.

After Inhalation

Remove victim from exposure to fresh air. Keep person at rest. Provide oxygen if person is not breathing. Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.

After Skin Contact

Remove all contaminated clothing and wash before reuse.
Wash contaminated skin with water and soap and rinse thoroughly.
Seek immediate medical advice.

After Eye Contact

Immediately bathe eyes for 15 minutes under running water.
Immediately remove contact lenses if present. Continue rinsing.
Seek immediate medical advice.

After Swallowing

If victim is unconscious; never give anything by mouth.
If victim is conscious; rinse out mouth and give victim small amounts of water.
Seek medical treatment in case of complaints.

After Exposure Seek medical treatment in case of complaints.

Information for Doctor Have chemical containers, labels and/or (M)SDS ready when calling or visiting a medical center.

Indication of any Immediate Medical Attention and Special Treatment Needed

After frequent or high intense exposure, the following medical tests are recommended:
eye tests
skin tests
Check section 11 Toxicological Information for further relevant information.

Additional Information

For additional information, please consult the corresponding first aid measures in the most current version of Emergency Response Guidebook which is produced by the US Department of Transportation.

5 Fire-fighting measures

Extinguishing Media

Suitable Extinguishing Agent(s)

Use fire fighting measures and extinguishing agents that suit the environment.
In case of fire, suitable extinguishing agents are:
Alcohol resistant foam.
Dry chemical or fire-extinguishing powder.
Carbon dioxide (CO₂).
Water spray or water fog.

Unsuitable Extinguishing Agent(s) Water with full jet

Firefighting Procedures

Isolate fire and deny unnecessary entry.
Immediately withdraw all personnel from the area in case of rising sound from venting safety device.
Eliminate all ignition sources if safe to do so.
Do not extinguish fire unless flow can be stopped.
Fight fire remotely due to the risk of explosion.
Burning liquids may be moved by flushing with water; protect personnel and minimize property damage.
Contain fire water runoff if possible to prevent environmental pollution.

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Print Date 05/19/2015

Revision Date 05/19/2015

Trade Name: EP1305LV Black A

(Contd. of page 3)

Fight fire from protected location or safe distance.
Contain fire water runoff if possible to prevent environmental pollution.

Special Hazards Arising in Fire

Will not burn unless preheated.

In case of fire, following can be released:

Phenolic compounds

Noxious fumes.

Formaldehyde, a skin and lung sensitizer and a regulated carcinogen, may be formed during fires.

Carbon dioxide (CO₂) and Carbon monoxide (CO)

Advice for Firefighters

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA fire brigades standard (29 CFR 1910.156).

As with any fire, wear positive-pressure self-contained breathing apparatus and full protective gear that are NIOSH approved.

Additional Information Be Caution! Finely dispersed substance may form explosive mixtures in air.

6 Accidental release measures

Personal Precautions

Do not breathe gas, vapors, dusts or mists if their inhalable particles occur during use.

Ensure personnel take precautions for their personal protection during clean up; see Section 8 for the specific requirements.

Environmental Precautions

Keep away from sewage system or other water courses; do not penetrate ground/soil.

Inform respective authorities in case of any seepage to the environment.

Cleaning Up Methods

Ensure adequate ventilation.

Eliminate all ignition sources.

Keep unauthorized personnel away.

For large spills:

Shut off source of leak if safe to do so.

Dike and contain.

Remove with vacuum trucks or pump to storage/salvage vessels.

Allow molten product to cool.

Absorb residues with liquid-binding materials.

Avoid confined spaces, such as sewers, because of the possibility of an explosion.

For small spills:

Ventilate and wash area after clean-up is complete.

Collect spills in suitable and properly labeled containers.

Do not use solvents unless following safe handling practices and within the recommended exposure guidelines.

Dispose contaminated chemicals as waste according to Section 13.

Additional Information No further relevant information.

7 Handling and storage

Handling

Precautions for Safe Handling

Obtain special instruction before use; do not handle until all safety precautions have been read and understood.

Do not breathe gas, vapors, dusts or mists if their inhalable particles occur during handling.

Wear respiratory protection when handling.

Keep away from incompatible material(s).

Avoid any release into the environment.

Observe all the personal protection requirements in Section 8.

Information about Protection Against Explosions and Fires

Will not burn unless preheated.

Keep away from heat, sparks, open flame and other ignition sources during handling.

Dust can combine with air to form an explosive mixture.

(Contd. on page 5)

Safety Data Sheet
acc. to OSHA HCS

Print Date 05/19/2015

Revision Date 05/19/2015

Trade Name: EP1305LV Black A

(Contd. of page 4)

Storage

Requirements to be Met by Storerooms and Receptacles

Store in a well-ventilated place; provide ventilation for receptacles.
Keep stored in accordance with local, regional, national, and international regulations.

Information about Storage in One Common Storage Facility

Store away from incompatible material(s).
Store away from foodstuffs.
Avoid release to the environment.

Additional Information No further relevant information.

8 Exposure controls/personal protection

Engineering Measures or Controls

Exposure Limit Values that Require Monitoring at the Workplace

1333-86-4 Carbon black

PEL	Long-term value: 3.5 mg/m ³
REL	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m ³ *inhalable fraction

Other Engineering Measures or Controls

Ventilation rates should be matched to conditions.
If applicable, use process enclosure(s), local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.

Personal Protective

General Protective and Hygienic Measures

Avoid any contact with eye.
Do not eat, drink or smoke during work.
Keep food, drink or feed away from working area.
Contaminated work clothing is not allowed out of workplace.
Clean hands and exposed skin thoroughly after work and before breaks.

Personal Protective Equipment (PPE)

Breathing Equipment

Caution! Improper use of respirators is dangerous.
In case of brief exposure or low pollution, use a respiratory filter device.
In case of intensive or longer exposure, use a positive-pressure respiratory protective device that is independent of circulating air.

Hand Protection



Protective gloves

Selection of glove material should take into consideration the penetration times, rates of diffusion, and the degradation.

Suggested glove type(s):

- Nitrile Gloves
- Butyl Rubber Gloves

Eye Protection



Tightly sealed goggles

Body Protection No relevant information.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/19/2015

Revision Date 05/19/2015

Trade Name: EP1305LV Black A

(Contd. of page 5)

Additional Information

All protective clothing (suits, gloves, footwear, headgear) should be clean, available every day, and put on before work.
 The Engineering measures or controls, and PPE recommendations are only guidelines and may not apply to every situation. For additional information, please consult the corresponding requirements under OSHA 29 CFR 1910.94-95, and 29 CFR 1910.132-138.

9 Physical and chemical properties

Information on Basic Physical and Chemical Properties
Appearance:

· Form:	Liquid
· Color:	Black
· Odor:	Mild epoxy odor
· Odor Threshold:	Not determined.

· **PH-Value:** Not determined.

Change in Condition:

· Melting Point:	Not determined.
· Boiling Point:	>200 °C (>392 °F)
· Flash Point:	>200 °C (>392 °F)
· Decomposition Temperature:	Not determined.
· Auto-ignition Temperature:	Not determined.
· Flammability:	Not determined.
· Explosion:	Not determined.
· Explosion Limits:	
· Lower:	Not determined.
· Upper:	Not determined.

· Vapor Pressure:	Not determined.
· Vapor Density:	not determined
· Density at 25 °C (77 °F):	1.15 g/cm ³ (9.597 lbs/gal)
· Solubility in or Miscibility with	
· Water:	Not miscible or difficult to mix.
· Segregation coefficient LogPow (n-octanol/water):	Not determined.
· Viscosity:	
· Dynamic at 20 °C (68 °F):	45000 mPas
· Kinematic:	Not determined.

· **Additional Information** No further relevant information.

10 Stability and reactivity

- **Physical Hazard(s)** Not a regulated reactive or physical hazard under GHS.
- **Hazardous Reactivity and Chemical Stability** Stable under normal conditions of use, storage and temperatures.
- **Thermal Decomposition and Conditions to be Avoided**
 Keep away from incompatible material(s).
 Thermally decomposes during fire or high heat; keep away from heat, sparks, open flame and other ignition sources.
- **Possibility of Other Hazardous Reaction(s)** No further relevant information available.
- **Incompatible Material(s)**
 Amines.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/19/2015

Revision Date 05/19/2015

Trade Name: EP1305LV Black A

(Contd. of page 6)

Oxidizing agents, Acids, Bases

Hazardous Decomposition Product(s)

Thermally decomposes during fire or very high heat. See Section 5 for fire hazards evolved during thermal decomposition.

Hazardous Polymerization Product(s) No relevant information.

Additional Information No further relevant information.

11 Toxicological information

For detailed Toxicological Information please email the Product Safety Department.

Acute Toxicity
Oral
25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Oral	LD50	11400 mg/kg (rat) 15600 mg/kg (mouse) Reference: NLM Toxnet (2010).
------	------	---

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Oral	LD50	> 5000 mg/kg (rat) Reference: Hexion (M)SDS (2003).
------	------	--

Potential Health Effect(s): Not a classified acute oral hazard.

Dermal
25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Dermal	LD50	20000 mg/kg (rabbit) (Test guideline not available) > 1270 mg/kg (mouse) > 2000 mg/kg (rat) > 1600 mg/kg (rabbit); however, there was no fixed test result available; classification was not possible without further information. Reference: Royce (M)SDS (2011) and ChemID (2010).
--------	------	--

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Dermal	LD50	> 2000 mg/kg (rabbit) Reference: Hexion (M)SDS (2003).
--------	------	---

Potential Health Effect(s): No further relevant information available; classification is not possible.

Inhalative
25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Inhalative	LC50/4 h	(Test species: n/a) (Toxicity not expected based on the acute oral data)
------------	----------	--

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Inhalative	LC50/4 h	(No data available)
------------	----------	---------------------

Potential Health Effect(s):

Not a classified acute inhalative hazard.

No further relevant information; classification is not possible.

Skin Corrosion or Irritation
25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Corrosion/Irritation	irritating (rabbit) Acute skin irritation was mild, through repeated and prolonged exposure may cause severe irritation. The substance was classified as Category 2 by GHS-J. Reference: HSNO CCID (2010) and GHS-J (2006).
----------------------	--

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Corrosion/Irritation	slightly irri. (Test species: n/a) Based on manufacturer's test result, the substance was slightly irritating to skin (Category 3). Reference: Hexion (M)SDS (2003).
----------------------	--

Potential Health Effect(s):

Causes skin irritation.

In contact with skin, may cause:

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Print Date 05/19/2015

Revision Date 05/19/2015

Trade Name: EP1305LV Black A

(Contd. of page 7)

redness and pain

Eye Serious Damage or Irritation

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Damage/Irritation irritating (rabbit)

The substance caused eye irritation (Category 2A) based on the dermal effect to rabbit skin.

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Damage/Irritation (No data available)

Potential Health Effect(s):

Causes serious eye irritation.

In contact with eye, may cause:

redness and pain

Respiratory or Skin Sensitization

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Sensitization Skin

sensitizing (Human)

Based on positive results from skin sensitization tests on human volunteers and guinea pigs, GHS-J classified the substance as a dermal sensitizer.

Reference: GHS-J (2006).

Respiratory

(No data available)

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Sensitization Skin

sensitizing (Test species: n/a)

Based on manufacturer's test result, the substance was a skin sensitizer, and the sensitization can be severe in susceptible individuals.

Reference: Hexion (M)SDS (2003).

Respiratory

(No data available)

Potential Health Effect(s):

May cause an allergic skin reaction.

No relevant information for respiratory sensitization; classification is not possible.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Germ Cell Mutagenicity

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Mutagenicity positive (Chinese hamster lung fibroblast cells) (In Vitro (Chromosomal Aberration))

In Vitro (Chromosomal Aberration; Chinese hamster lung fibroblast cells) - Positive without metabolic activation; negative with metabolic activation.

Positive (salmonella typhimurium) (In Vitro (Ames assay)). Due to the absence from In Vivo tests, it was not possible to make a conclusion of mutagenicity of the substance.

Reference: NLM CCRIS (2010).

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Mutagenicity (No data available)

Potential Health Effect(s): No further relevant information; classification is not possible.

Carcinogenicity

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Carcinogenicity negative (Test species: n/a) (Not listed by ACGIH, IARC, NTP, or OSHA)

(Mouse)

1 out of 4 cases with female mice showed positive carcinogenic results after a repeated dermal application with 10% concentration of the substance for two years. When considering all of the evidence, the substance was not classified as a carcinogen.

Reference: Dow (M)SDS (2010).

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Carcinogenicity negative (Test species: n/a) (not listed as a Carcinogen by NTP, IARC or OSHA)

Potential Health Effect(s): Not a known Carcinogen.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/19/2015

Revision Date 05/19/2015

Trade Name: EP1305LV Black A

(Contd. of page 8)

Reproductive Toxicity

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Reproductive Toxi. negative (Test species: n/a) (no reproductive or developmental effect observed)
 There was no reproductive or developmental effect observed at dosing levels that were toxic to parental animals.
 Reference: GHS-J (2006).

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Reproductive Toxi. (No data available)

Potential Health Effect(s): Not a known Reproductive hazard.

Specific Target Organ Toxicity - Single Exposure

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

STOT-Single Target: None (Rats and Mice) (No effect after single oral doses)
 Somnolence (general depressed activity) and dyspnea were observed after a single oral application with 11400 mg/kg to rats, or 15600 mg/kg to mice of the substance. However, the dose levels were both outside of the guidance value ranges.
 Reference: NLM Toxnet (2010).

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

STOT-Single (No data available)

Potential Health Effect(s): Not a known hazard to organs upon single exposure.

Specific Target Organ Toxicity - Repeated Exposure

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

STOT-Repeated Target: N/A (guinea pig) (insufficient data for classification)
 With dermal application of the substance for 55 days, increased seromuroid concentrations, decreased lactate-dehydrogenase (LDH), and decreased leucynaphthylamidase (LNA) were observed in the test animals. Meanwhile, the substance caused a toxic effect on blood components of female guinea-pigs with greater effects on pregnant animals. However, there was no detail available regarding the dose level or test guideline, classification was thus not possible.
 Reference: HSNO CCID (2010).

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

STOT-Repeated (No data available)

Potential Health Effect(s): No further relevant information; classification is not possible.

Aspiration Hazard

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Aspiration Hazard (No data available)

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Aspiration Hazard (No data available)

Potential Health Effect(s): No relevant information; classification is not possible.

Additional Information No further relevant information.

12 Ecological information

Aquatic Environmental Toxicity

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Algae Toxicity (No data available)
 Crustacean Toxicity 1.4 - 1.7 mg/l (Daphnia magna (water flea)) (EC50 (48 hrs))
 Fish Toxicity 1.41 mg/l (Oryzias latipes (Rice fish)) (LC50 (96 hrs))
 3.1 mg/l (Pimephales promelas (fathead minnow)) (LC50 (96 hrs))
 Based on the non-rapid degradability and the acute LC50 < 10 mg/L, the substance is classified as a Chronic-2 environmental hazard.
 Reference: Dow (M)SDS (2010) and CHRIP (2010).

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Algae Toxicity (No data available)
 Crustacean Toxicity (No data available)
 Fish Toxicity (No data available)

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Print Date 05/19/2015

Revision Date 05/19/2015

Trade Name: EP1305LV Black A

(Contd. of page 9)

Aquatic Environmental Toxicity Assessment: Toxic to aquatic life with long lasting effects.

Degradability and Stability

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Biodegradation non-biodegrad. (Test species: n/a) (Biodegradation (OECD TG 302B; 28 days) = 12%)
(Activated Sludge) (OECD TG 301C; 4 weeks; Conc. 100 mg/L)
Biodegradation (Indirect Analysis from BOD) = 0%
Biodegradation (Direct Analysis from HPLC) = 0%
The substance is non-biodegradable.
Reference: Dow (M)SDS (2010) and CHRIP (2010).

Persistence (Test species: n/a) (This substance is persistent)
Reference: Canada DSL (2007) and CHRIP (2010).

Photodegradation 6.69E-11 cm³/molecule-sec (OH radical) (Half-life (T1/2) = 1.92 hrs)
However, photolysis in water is negligible.
Reference: Dow (M)SDS (2010).

Stability in water (No data available)

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

Biodegradation non-biodegrad. (Test species: n/a) (Non-biodegradable due to persistent property)
Based on the persistent assessment according to Canada DSL, the substance is expected to be non-degradable in the environment.

Persistence (Test species: n/a) (The substance is persistent)
Reference: Canada DSL (2007).

Photodegradation (No data available)

Stability in water (No data available)

Bioaccumulation and Distribution

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

BCF 0.56-42 (Cyprinus carpio) (The substance is low-bioaccumulative)
BCF (28 days; Concentration: 10 µg/L) = 0.56 - 0.67, 3.3 - 4.2
BCF (28 days; Concentration: 1 µg/L) = 5.6 - 6.8, 33 - 42
Reference: CHRIP (2010).

Koc 1800 - 4400 L/kg (soil)
Potential for mobility in soil is moderate.
Reference: Dow (M)SDS (2010).

LogPow 3.7 - 3.9 (Test species: n/a)
Reference: Dow (M)SDS (2010).

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

BCF (Test species: n/a) (The substance is not bioaccumulative)
Reference: Canada DSL (2007).

Koc (No data available)

LogPow (No data available)

Degradability and Bioaccumulation Assessment: Non-rapidly degradable, and low bioaccumulative.

Additional Information No further relevant information.

13 Disposal considerations

Hazardous Waste List

Description: It may be necessary to contain and dispose of the substance/mixture as a hazardous waste.

Waste Treatment Recommendation:

Generation of waste should be avoided or minimized wherever possible.

Chemical waste, even small quantities, is neither allowed to be poured down drains, sewage system or waterways; nor disposed with household garbage.

Dispose of contents/containers in accordance with local, regional, national, and international regulations.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/19/2015

Revision Date 05/19/2015

Trade Name: EP1305LV Black A

(Contd. of page 10)

Unused and Uncontaminated Packagings
Recommendation Dispose of according to your local waste regulations.

14 Transport information

UN-Number

DOT, ADR, IMDG, IATA UN3082

UN Proper Shipping Name

DOT, ADR, IMDG, IATA Environmentally hazardous substances, liquid, n.o.s. (Bisphenol-A-epichlorohydrin) epoxy resin

Transport hazard class(es)

DOT, IMDG, IATA


 Class Label 9 Miscellaneous dangerous substances and articles
9

ADR

 Class Label 9 (M6) Miscellaneous dangerous substances and articles
9

Packing group

DOT, ADR, IMDG, IATA III

Environmental Hazards:

 Marine Pollutant: Yes
Symbol (fish and tree)

Special Marking (ADR): Symbol (fish and tree)

Special Marking (IATA): Symbol (fish and tree)

Special Precautions:

 Warning: Miscellaneous dangerous substances and articles
 Danger Code (Kemler): 90
 EMS Number: F-A, S-F

Transport in Bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

Transport/Additional Information:
DOT

 Quantity limitations On passenger aircraft/rail: No limit
On cargo aircraft only: No limit

Remarks: Special marking with the symbol (fish and tree).

(Contd. on page 12)

US

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/19/2015

Revision Date 05/19/2015

Trade Name: EP1305LV Black A

(Contd. of page 11)

ADR**Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

IMDG**Limited quantities (LQ)**

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation":

UN3082, Environmentally hazardous substances, liquid, n.o.s. (Bisphenol-A-(epichlorohydrin) epoxy resin), 9, III

15 Regulatory information

USA Regulation Lists**SARA (Superfund Amendments and Reauthorization Act of 1986)****Section 302 (Extremely Hazardous Substances)**

None of the ingredients is listed.

Section 313 (Toxics Release Inventory (TRI) reporting)

None of the ingredients is listed.

Section 311/312 (Hazardous Chemical Inventory Reporting)

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin	A, C	70-80%
74398-71-3	1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid	A, C	10-20%
1333-86-4	Carbon black	A, C	0.1-<1%
2530-83-8	Glycidyloxypropyltrimethoxysilane	A, C	0.1-<1%

Hazard Abbreviations for SARA 311/312

A - Acute Health Hazard

C - Chronic Health Hazard

F - Fire Hazard

R - Reactive Hazard

S - Sudden Release of Pressure Hazard

TSCA (Toxic Substances Control Act)

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin
74398-71-3	1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid
1333-86-4	Carbon black
2530-83-8	Glycidyloxypropyltrimethoxysilane

Proposition 65**Chemicals Known to Cause Cancer**

1333-86-4 Carbon black

Chemicals Known to Cause Reproductive Toxicity for Females

None of the ingredients is listed.

Chemicals Known to Cause Reproductive Toxicity for Males

None of the ingredients is listed.

Chemicals Known to Cause Developmental Toxicity

None of the ingredients is listed.

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Print Date 05/19/2015

Revision Date 05/19/2015

Trade Name: EP1305LV Black A

(Contd. of page 12)

Carcinogenic Categories
EPA (Environmental Protection Agency)

None of the ingredients is listed.

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

TLV (Threshold Limit Value Established by ACGIH)

1333-86-4 Carbon black

A4

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

International Regulation Lists
Canadian Domestic Substance Listings:

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin
74398-71-3	1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid
1333-86-4	Carbon black
2530-83-8	Glycidylxypropyltrimethoxysilane

Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

Canadian Ingredient Disclosure list (limit 1%)

None of the ingredients is listed.

Chinese Chemical Inventory of Existing Chemical Substances:

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin
74398-71-3	1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid
1333-86-4	Carbon black
2530-83-8	Glycidylxypropyltrimethoxysilane

Japanese Existing and New Chemical Substance List:

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin
1333-86-4	Carbon black
2530-83-8	Glycidylxypropyltrimethoxysilane

Korean Existing Chemical Inventory:

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin
74398-71-3	1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid
1333-86-4	Carbon black
2530-83-8	Glycidylxypropyltrimethoxysilane

European Pre-registered substances:

25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin
74398-71-3	1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid
1333-86-4	Carbon black
2530-83-8	Glycidylxypropyltrimethoxysilane

REACH - Substances of Very High Concern (SVHC) List:

None of the ingredients is listed.

Restriction of Hazardous Substances Directive (RoHS) list:

None of the ingredients is listed.

US

(Contd. on page 14)

Safety Data Sheet acc. to OSHA HCS

Print Date 05/19/2015

Revision Date 05/19/2015

Trade Name: EP1305LV Black A

(Contd. of page 13)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department Issuing (M)SDS:** Product Safety Department

· **Contact:** msds@resinlab.com

· **Abbreviations and acronyms:**

ACGIH: American Conference of Governmental Industrial Hygienists

ACToR: US EPA Aggregated Computational Toxicology Resource

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road

BCF: Bioconcentration Factor

CAS: Chemical Abstracts Service (division of the American Chemical Society)

CCRIS: US NLM TOXNET Chemical Carcinogenesis Research Information System

CHRIP: Japan NITE Information on Biodegradation and Bioconcentration of the Existing Chemical Substances in the Chemical Risk Information Platform

DOT: US Department of Transportation

DSL: Canada Domestic Substance List

ECHA: European Chemicals Agency's Dissemination portal with information on chemical substances registered under REACH

HMIS: US National Paint & Coatings Association (NPCA) Hazardous Materials Identification System

HSDB: US NLM TOXNET Hazardous Substances Databank

HSNO CCID: New Zealand Hazardous Substances and New Organisms Chemical Classification Information Database

IARC: International Agency for Research on Cancer developed by United Nations World Health Organisation (WHO)

IATA-DGR: Dangerous Goods Regulations (DGR) by the International Air Transport Association (IATA)

ICAO-TI: Technical Instructions (TI) by the International Civil Aviation Organization (ICAO)

ICSC: International Chemical Safety Cards

IMDG: International Maritime Dangerous Goods; the principal international rules for International Carriage of Dangerous Goods by SEA under the Recommendations on the Transport of Dangerous Goods by United Nations (RTDG)

IUCLID: EU REACH International Uniform Chemical Information Database

Koc: Partition coefficient, soil Organic Carbon to water

LC50/LD50: Lethal Concentration/Dose, 50 percent

N/a: Not available or Not applicable

NFPA: US National Fire Protection Association

NIOSH: US National Institute of Occupational Safety and Health

NITE: National Institute of Technology and Evaluation, Japan

NLM TOXNET: US National Library of Medicine Toxicology Data Network

OECD: Organisation for Economic Co-operation and Development

OSHA: US Occupational Safety and Health Administration

P: Marine Pollutant

RCRA: Resource Conservation and Recovery Act (USA)

REACH: EU Registry, Evaluation and Authorisation of Chemicals

RID: the Regulations Concerning the International Carriage of Dangerous Goods by Rail; published by the Central Office for International Carriage by Rail (OTIF)

RTDG: the Recommendations on the Transport of Dangerous Goods by United Nations (UN)

RTECS: US Registry of Toxic Effects of Chemical Substances

SARA: US Superfund Amendments and Reauthorization Act

SIDS: OECD existing chemicals Screening Information Data Sets

SVHC: EU ECHA Substance of Very High Concern

TEEL: Temporary Emergency Exposure Limit developed by US Subcommittee on Consequence Assessment and Protective Actions (SCAPA) of US Department of Energy (DOE)

TOXLINE: US NLM bibliographic database search system

TSCA: US Toxic Substance Control Act

ESIS: European Chemical Substances Information System

· **Date of preparation / last revision** 05/19/2015 / 1