

Safety Data Sheet acc. to OSHA HCS




Printing date 03/16/2018


Reviewed on 03/16/2018

1 Identification

- **Product identifier**
 - **Trade name:** EP1296 Black A
 - **Recommended use:** Epoxy Resin
 - **Restrictions on use:** For industrial use only
- **Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
ResinLab, LLC
N109 W13300 Ellsworth Drive
Germantown, WI 53022
1-877-259-1669
www.resinlab.com
 - **Information Department:** Product Safety Department: msds@resinlab.com
 - **Emergency Telephone Number:**
North America - Chemtrec: 1-800-424-9300 (24 hours)
International - Chemtrec: 01-703-527-3887 (24 hours)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Muta. 2 H341 Suspected of causing genetic defects.
- **Label elements**
 - **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
 - **Hazard pictograms**


 GHS07 GHS08
 - **Signal word** Warning
 - **Hazard-determining components of labeling:**
Bisphenol-A-(epichlorohydrin) epoxy resin
o-Cresyl glycidyl ether
 - **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
 - **Precautionary statements**
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Classification system:**
 - **NFPA System**
 - **NFPA ratings (scale 0 - 4)**

 Health = 2
Fire = 1
Reactivity = 0

 NFPA special hazards (water reactivity and oxidizing property): None
 - **HMIS System**
 - **HMIS-ratings (scale 0 - 4)**

 HEALTH 2
FIRE 1
REACTIVITY 0
 Health = 2
Fire = 1
Reactivity = 0
- **Other hazards**
 - **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

US

(Contd. on page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/16/2018

Reviewed on 03/16/2018

Trade name: EP1296 Black A

(Contd. of page 1)

3 Composition/information on ingredients

Chemical characterization: Mixtures

Dangerous components:

CAS: 1317-65-3 EINECS: 215-279-6 RTECS: EV 9580000	Calcium Carbonate	40-50%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8	Bisphenol-A-(epichlorohydrin) epoxy resin Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	30-40%
CAS: 2210-79-9 EINECS: 218-645-3 Index number: 603-056-00-X RTECS: TZ3700000	o-Cresyl glycidyl ether Muta. 2, H341 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Skin Sens. 1, H317	≥5-<10%
CAS: 1333-86-4 EINECS: 215-609-9 RTECS: FF5800000	Carbon black	0.1-1%
CAS: 14808-60-7 EINECS: 238-878-4 RTECS: VV 7330000	Quartz	0.1-1%
CAS: 67762-90-7 EC number: 614-122-2	Siloxanes and Silicones, di-Me, reaction products with silica	0.1-1%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 RTECS: EO 1400000	1-Butyl alcohol Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥0-<0.1%
CAS: 64742-48-9 EINECS: 265-150-3 Index number: 649-327-00-6	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226 Asp. Tox. 1, H304	≥0-<0.1%
CAS: 140-88-5 EINECS: 205-438-8 Index number: 607-032-00-X RTECS: AT 0700000	ethyl acrylate Flam. Liq. 2, H225 Acute Tox. 3, H331 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335 Aquatic Acute 3, H402; Aquatic Chronic 3, H412	≥0-<0.1%

Additional information:

If the chemical name/CAS number is proprietary and or weight percentage is listed as a range, the specific chemical identity and or percentage of composition has been withheld as a trade secret.

4 First-aid measures

Description of first aid measures

General information: Keep warm, position comfortably and cover well.

After inhalation:

Remove victim from exposure to fresh air. Keep person at rest. Provide oxygen if person is not breathing.

Supply fresh air and if symptoms occur call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Remove all contaminated clothing and wash before reuse.

If skin rash or irritation occurs, seek medical advice.

After eye contact:

Immediately flush opened eyes with water for 5 minutes, then remove contact lenses if present, continue flushing for at least another 15 minutes.

If symptoms develop seek medical attention.

After swallowing:

If victim is unconscious; never give anything by mouth.

If victim is conscious, rinse out mouth with water.

Get medical attention if you feel unwell.

Information for doctor:

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed

Check section 11 Toxicological Information for further relevant information.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

Use fire fighting measures that suit the environment.

Fire-extinguishing powder

Alcohol resistant foam

Carbon dioxide

dry chemical

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture

Will not burn unless preheated.

In case of fire, the following can be released:

Aldehydes

Phenolics

Carbon dioxide (CO₂) and Carbon monoxide (CO)

(Contd. on page 3)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/16/2018

Reviewed on 03/16/2018

Trade name: EP1296 Black A

(Contd. of page 2)

- **Advice for firefighters**

- **Protective equipment:**

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA fire brigades standard (29 CFR 1910.156).

As with any fire, wear positive-pressure self-contained breathing apparatus and full protective gear that are NIOSH approved.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective clothing.

Do not breathe gas, vapors, dusts or mists if their inhalable particles occur during use.

- **Environmental precautions:** Inform respective authorities in case of seepage into water course or sewage system.

- **Methods and material for containment and cleaning up:**

For large spills: provide diking or containment to minimize spreading. If possible pump and store material in appropriate container.

For small spills: Ventilate and wash area. Collect spills and absorbant material in appropriate container.

Ensure adequate ventilation.

Allow molten product to cool.

Non sparking tools should be used.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Do not breathe dust created by cutting, sanding, grinding or machining.

Open and handle receptacle with care.

Prevent formation of aerosols.

Keep away from incompatible material(s).

Avoid any release into the environment.

Do not breathe dust/fumes/mist/vapor/spray.

Avoid contact with eyes, skin and clothing.

Keep away from heat, sparks, flames and ignition sources.

Observe all the personal protection requirements in Section 8.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Provide ventilation for receptacles.

Keep stored in accordance with local, regional, national, and international regulations.

8 Exposure controls/personal protection

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

1317-65-3 Calcium Carbonate

TEEL Short-term value: 15.0 mg/m³

Long-term value: 60.0 mg/m³

SCAPA, 2008

1333-86-4 Carbon black

PEL Long-term value: 3.5 mg/m³

REL Long-term value: 3.5* mg/m³

*0.1 in presence of PAHs; See Pocket Guide Apps.A+C

TLV Long-term value: 3* mg/m³

*inhalable fraction

14808-60-7 Quartz

PEL see Quartz listing

REL Long-term value: 0.05* mg/m³

*respirable dust; See Pocket Guide App. A

TLV Long-term value: 0.025* mg/m³

*as respirable fraction

67762-90-7 Siloxanes and Silicones, di-Me, reaction products with silica

OSHA PEL Short-term value: 15 mg/m³

US ACGIH Short-term value: 10 mg/m³

71-36-3 1-Butyl alcohol

PEL Long-term value: 300 mg/m³, 100 ppm

REL Ceiling limit value: 150 mg/m³, 50 ppm

Skin

TLV Long-term value: 61 mg/m³, 20 ppm

64742-48-9 Naphtha (petroleum), hydrotreated heavy

OSHA Short-term value: 400 mg/m³

140-88-5 ethyl acrylate

PEL Long-term value: 100 mg/m³, 25 ppm

Skin

(Contd. on page 4)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 03/16/2018

Reviewed on 03/16/2018

Trade name: EP1296 Black A

(Contd. of page 3)

REL	See Pocket Guide App. A
TLV	Short-term value: 61 mg/m ³ , 15 ppm Long-term value: 20 mg/m ³ , 5 ppm

· **Additional Occupational Exposure Limit Values for possible hazards during processing:** None.

· **Exposure controls**

If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.

If exposure limits have not been established, maintain airborne levels to an acceptable level.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Be sure to clean skin thoroughly after work and before breaks.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Avoid contact with the eyes and skin.

· **Personal Protective Equipment (PPE)**

· **Breathing equipment:**

Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits.

Use a NIOSH approved air-purifying organic vapor respirator if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air supplied respirator. Observe OSHA regulations (29CFR 1910.134) for respirator use.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**



Chemical resistant gloves

· **Eye protection:**



Safety Glasses with side shields

· **Body protection:** Appropriate chemical resistant clothing.

· **Limitation and supervision of exposure into the environment**

The Engineering measures or controls, and PPE recommendations are only guidelines and may not apply to every situation. For additional information, please consult the corresponding requirements under OSHA 29 CFR 1910.94-95, and 29 CFR 1910.132-138.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· **Form:**

Liquid

· **Color:**

Black

· **Odor:**

Mild epoxy odor

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

· **Melting point/Melting range:**

Undetermined.

· **Boiling point/Boiling range:**

>100 °C (>212 °F)

· **Flash point:**

>93 °C (>199.4 °F)

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

Not determined.

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

Product does not present an explosion hazard.

· **Explosion limits:**

· **Lower:**

Not determined.

· **Upper:**

Not determined.

· **Vapor pressure:**

Not determined.

· **Vapor Density:**

not determined

· **Density at 20 °C (68 °F):**

1.5 g/cm³ (12.52 lbs/gal)

· **Relative density**

Not determined.

· **Vapor density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with**

· **Water:**

Not miscible or difficult to mix.

(Contd. on page 5)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 03/16/2018

Reviewed on 03/16/2018

Trade name: EP1296 Black A

(Contd. of page 4)

- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
 - **Dynamic:** Not available.
 - **Kinematic:** Not available.
 - **VOC content:** 0.06 %
0.8 g/l / 0.01 lb/gl

10 Stability and reactivity

- **Reactivity** Not a regulated physical hazard under GHS.
- **Hazardous Reactivity and Chemical Stability** Stable under normal conditions of use, storage and temperatures.
- **Thermal decomposition / conditions to be avoided:**
To avoid thermal decomposition do not overheat.
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** In contact with incompatible materials.
- **Conditions to avoid** Keep away from heat, sparks, flame and any other ignition sources.
- **Incompatible materials:**
Oxidizing agents
Mercaptans
Acids
Amines
Bases (Alkalis)
- **Hazardous decomposition products:**
Possible in traces.
Irritating fumes

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

1317-65-3 Calcium Carbonate

Oral	LD50	6,450 mg/kg (rat)
Dermal	LD50	mg/kg No data available.
Inhalative	LC50/4 h	mg/l No data available.

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

Oral	LD50	11,400 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit) (Test guideline not available)
Inhalative	LC50/4 h	mg/l (Test species: n/a) (Toxicity not expected based on the acute oral data)

2210-79-9 o-Cresyl glycidyl ether

Oral	LD50	4,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	mg/l (rat) (Non-toxic; LC50 exceeded the saturated vapor value)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1333-86-4	Carbon black	2B
14808-60-7	Quartz	1
103-11-7	2-ethylhexyl acrylate	3
140-88-5	ethyl acrylate	2B

- **NTP (National Toxicology Program)**

14808-60-7	Quartz	K
------------	--------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/16/2018

Reviewed on 03/16/2018

Trade name: EP1296 Black A

(Contd. of page 5)

12 Ecological information

Toxicity
Aquatic toxicity:

1317-65-3 Calcium Carbonate

EC50 mg/kg

mg/kg (rabbit) (Draize test)

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

EC50 mg/kg (rabbit)

2210-79-9 o-Cresyl glycidyl ether

EC50 mg/kg (rabbit) (Read-across from CAS 26447-14-3; OECD TG 404)

Persistence and degradability No further relevant information available.

Behavior in environmental systems:
Bioaccumulative potential No data available.

Mobility in soil No further relevant information available.

Additional ecological information: The product is non-rapid degradable, and low or not highly bioaccumulative.

General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Results of PBT and vPvB assessment
PBT: None of the ingredients is listed.

vPvB: None of the ingredients is listed.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods
RCRA Waste:

71-36-3 1-Butyl alcohol

U031 (n-Butyl alcohol (I)) ≥ 0 - $<0.1\%$
Recommendation:

Must be specially treated adhering to official regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:
Recommendation: Dispose of according to your local waste regulations.

14 Transport information

UN-Number
DOT
IMDG, IATA
not regulated
UN3082
UN proper shipping name
DOT
IMDG
not regulated
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S. (Bisphenol-A-(epichlorohydrin) epoxy resin, o-Cresyl
glycidyl ether). MARINE POLLUTANT
IATA
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S. (Bisphenol-A-(epichlorohydrin) epoxy resin, o-Cresyl
glycidyl ether)
Transport hazard class(es)
DOT
Class

not regulated

IMDG, IATA

Class
Label
9 Miscellaneous dangerous substances and articles
9
Packing group
DOT
IMDG, IATA
not regulated
III
Environmental hazards:

Product contains environmentally hazardous substances: Bisphenol-A-(epichlorohydrin) epoxy resin

Special precautions for user
Danger code (Kemler):
EMS Number:
Stowage Category
Warning: Miscellaneous dangerous substances and articles
90
F-A,S-F
A

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/16/2018

Reviewed on 03/16/2018

Trade name: EP1296 Black A

(Contd. of page 6)

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:**
 - **DOT**
 - **Remarks:** Not DOT regulated in packages less than 5L.
 - **IMDG**
 - **Limited quantities (LQ)** 5L
 - **Excepted quantities (EQ)** Code: E1
 - Maximum net quantity per inner packaging: 30 ml
 - Maximum net quantity per outer packaging: 1000 ml
- **UN "Model Regulation":** UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (BISPHENOL-A-(EPICHLOROHYDRIN) EPOXY RESIN, O-CRESYL GLYCIDYL ETHER), 9, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **SARA Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **SARA Section 313 (Specific toxic chemical listings):**

71-36-3	1-Butyl alcohol	≥0-<0.1%
140-88-5	ethyl acrylate	≥0-<0.1%

- **SARA Section 311/312 (Hazardous Chemical Inventory Reporting)**

1317-65-3	Calcium Carbonate	A, C	40-50%
25068-38-6	Bisphenol-A-(epichlorohydrin) epoxy resin	A, C	30-40%
2210-79-9	o-Cresyl glycidyl ether	A, C	≥5-<10%
1333-86-4	Carbon black	A, C	0.1-1%

- **Hazard Abbreviations for SARA 311/312**

A - Acute Health Hazard
 C - Chronic Health Hazard
 F - Fire Hazard
 R - Reactive Hazard
 S - Sudden Release of Pressure Hazard

- **TSCA 8 (b) Inventory:**

All ingredients are listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

1333-86-4	Carbon black
14808-60-7	Quartz
140-88-5	ethyl acrylate

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

71-36-3	1-Butyl alcohol	D
---------	-----------------	---

- **TLV (Threshold Limit Value established by ACGIH)**

1333-86-4	Carbon black	A4
14808-60-7	Quartz	A2
140-88-5	ethyl acrylate	A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

14808-60-7	Quartz
140-88-5	ethyl acrylate

- **International Regulation Lists**

- **GHS label elements** GHS label elements

- **REACH - Substances of Very High Concern (SVHC) List:**

None of the ingredients is listed.

- **Restriction of Hazardous Substances Directive (RoHS) list:**

None of the ingredients is listed.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 8)

Safety Data Sheet
acc. to OSHA HCS

Printing date 03/16/2018

Reviewed on 03/16/2018

Trade name: EP1296 Black A

(Contd. of page 7)

- **Department Issuing (M)SDS:** Product Development Department
- **Contact:** msds@resinlab.com
- **Date of preparation / last revision** 03/16/2018 / 3
- * **Data compared to the previous version altered.**

US