

Safety Data Sheet acc. to OSHA HCS

Printing date 06/06/2017

Reviewed on 06/06/2017

1 Identification

- **Product identifier**
 - **Trade name:** EP1282 Black A
 - **Application of the substance / the mixture** Epoxy Resin
- **Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
ResinLab, LLC
N109 W13300 Ellsworth Drive
Germantown, WI 53022
1-877-259-1669
www.resinlab.com
 - **Information Department:** Product Safety Department: msds@resinlab.com
 - **Emergency Telephone Number:**
North America - Chemtrec: 1-800-424-9300 (24 hours)
International - Chemtrec: 01-703-527-3887 (24 hours)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
- **Label elements**
 - **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
 - **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard-determining components of labeling:**
Bisphenol-A-(epichlorohydrin) epoxy resin
1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
- **Precautionary statements**
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves / eye protection / face protection.
IF ON SKIN: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Wash contaminated clothing before reuse.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**
 - **NFPA System**
 - **NFPA ratings (scale 0 - 4)**



NFPA special hazards (water reactivity and oxidizing property): None

- **HMIS System**
 - **HMIS-ratings (scale 0 - 4)**



- **Other hazards**
 - **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

Safety Data Sheet acc. to OSHA HCS

Printing date 06/06/2017

Reviewed on 06/06/2017

Trade name: EP1282 Black A

(Contd. of page 1)

3 Composition/information on ingredients

- Chemical characterization: Mixtures

- Dangerous components:

| | | |
|---|--|--------|
| CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 | Bisphenol-A-(epichlorohydrin) epoxy resin Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317 | 80-90% |
| CAS: 74398-71-3 EC number: 616-085-8 | 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid Skin Sens. 1, H317 | 10-20% |
| CAS: 1333-86-4 EINECS: 215-609-9 RTECS: FF580000 | Carbon black | 1-2.5% |

- Additional information:

If the chemical name/CAS number is proprietary and or weight percentage is listed as a range, the specific chemical identity and or percentage of composition has been withheld as a trade secret.

4 First-aid measures

- Description of first aid measures

- General information: Keep warm, position comfortably and cover well.

- After inhalation:

Supply fresh air and if symptoms occur call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact:

Flush skin thoroughly. Remove all contaminated clothing and shoes. Continue to rinse skin for 15 minutes. Obtain medical attention if symptoms develop. Wash all contaminated clothing and shoes before reuse.

- After eye contact:

Immediately flush opened eyes with water for 5 minutes, then remove contact lenses if present, continue flushing for at least another 15 minutes.

If symptoms develop seek medical attention.

- After swallowing:

If victim is unconscious; never give anything by mouth.

Rinse out mouth and then drink plenty of water.

Get medical attention if you feel unwell.

- Information for doctor:

- Most important symptoms and effects, both acute and delayed No further relevant information available.

- Indication of any immediate medical attention and special treatment needed

Check section 11 Toxicological Information for further relevant information.

5 Fire-fighting measures

- Extinguishing media

- Suitable extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet

- Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon dioxide (CO₂) and Carbon monoxide (CO)

Phenolic compounds

- Advice for firefighters

- Protective equipment:

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA fire brigades standard (29 CFR 1910.156).

As with any fire, wear positive-pressure self-contained breathing apparatus and full protective gear that are NIOSH approved.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Do not breathe gas, vapors, dusts or mists if their inhalable particles occur during use.

- Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

- Methods and material for containment and cleaning up:

For large spills: provide diking or containment to minimize spreading. If possible pump and store material in appropriate container.

For small spills: Ventilate and wash area. Collect spills and absorbant material in appropriate container.

Ensure adequate ventilation.

Allow molten product to cool.

Non sparking tools should be used.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

7 Handling and storage

- Handling:

- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 3)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 06/06/2017

Reviewed on 06/06/2017

Trade name: EP1282 Black A

(Contd. of page 2)

Prevent formation of aerosols.
 Keep away from incompatible material(s).
 Avoid any release into the environment.
 For industrial or professional use only
 Do not breathe dust/fumes/mist/vapor/spray.
 Avoid contact with eyes, skin and clothing.
 Keep away from heat, sparks, flames and ignition sources.
 Observe all the personal protection requirements in Section 8.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Provide ventilation for receptacles.
 Keep stored in accordance with local, regional, national, and international regulations.

8 Exposure controls/personal protection

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

1333-86-4 Carbon black

| | |
|-----|--|
| PEL | Long-term value: 3.5 mg/m ³ |
| REL | Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C |
| TLV | Long-term value: 3* mg/m ³ *inhalable fraction |

- **Additional Occupational Exposure Limit Values for possible hazards during processing:** None.

- **Exposure controls**

If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.

If exposure limits have not been established, maintain airborne levels to an acceptable level.

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Be sure to clean skin thoroughly after work and before breaks.
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Avoid contact with the eyes and skin.

- **Personal Protective Equipment (PPE)**

- **Breathing equipment:**

Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits.

Use a NIOSH approved air-purifying organic vapor respirator if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air supplied respirator. Observe OSHA regulations (29CFR 1910.134) for respirator use.

- **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**



Chemical resistant gloves

- **Eye protection:**



Safety Glasses with side shields

- **Body protection:** Appropriate chemical resistant clothing.

- **Limitation and supervision of exposure into the environment**

The Engineering measures or controls, and PPE recommendations are only guidelines and may not apply to every situation. For additional information, please consult the corresponding requirements under OSHA 29 CFR 1910.94-95, and 29 CFR 1910.132-138.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:**

Liquid

- **Color:**

Black

- **Odor:**

Mild epoxy odor

- **Odor threshold:**

Not determined.

- **pH-value:**

Not determined.

(Contd. on page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/06/2017

Reviewed on 06/06/2017

Trade name: EP1282 Black A

(Contd. of page 3)

| | |
|---|---|
| · Change in condition | |
| · Melting point/Melting range: | Undetermined. |
| · Boiling point/Boiling range: | Undetermined. |
| · Flash point: | >93 °C (>199 °F) |
| · Flammability (solid, gaseous): | Not applicable. |
| · Ignition temperature: | Not determined. |
| · Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | Product does not present an explosion hazard. |
| · Explosion limits: | |
| · Lower: | Not determined. |
| · Upper: | Not determined. |
| · Vapor pressure: | Not determined. |
| · Vapor Density: | not determined |
| · Density at 20 °C (68 °F): | 1.14 g/cm ³ (9.513 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with | |
| · Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| · Dynamic: | Not available. |
| · Kinematic: | Not available. |
| · VOC content: | 0.0 g/l / 0.00 lb/gl |

10 Stability and reactivity

- **Reactivity** Not a regulated physical hazard under GHS.
- **Hazardous Reactivity and Chemical Stability** Stable under normal conditions of use, storage and temperatures.
- **Thermal decomposition / conditions to be avoided:**
To avoid thermal decomposition do not overheat.
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions** In contact with incompatible materials.
- **Conditions to avoid** Keep away from heat, sparks, flame and any other ignition sources.
- **Incompatible materials:**
Oxidizing agents
Mercaptans
Acids
Amines
Bases (Alkalis)
- **Hazardous decomposition products:**
Possible in traces.
Refer to section 5.
- **Additional information:**
As long as the prescribed application concentrations are maintained there is no danger that stable emulsions will form.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
· **LD/LC50 values that are relevant for classification:**
Not a classified acute oral hazard.

25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin

| | | |
|------------|----------|--|
| Oral | LD50 | 11400 mg/kg (rat) |
| Dermal | LD50 | 20000 mg/kg (rabbit) (Test guideline not available) |
| Inhalative | LC50/4 h | (Test species: n/a) (Toxicity not expected based on the acute oral data) |

74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid

| | | |
|------------|----------|--|
| Oral | LD50 | > 5000 mg/kg (rat) |
| Dermal | LD50 | > 2000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | (Test species: n/a) (Toxicity not expected based on the acute oral data) |

1333-86-4 Carbon black

| | | |
|------------|----------|--|
| Oral | LD50 | > 10000 mg/kg (rat) (Toxicity not anticipated under normal conditions) |
| Dermal | LD50 | > 3000 mg/kg (Test species: n/a) (Toxicity not anticipated under normal conditions) |
| Inhalative | LC50/4 h | not classified mg/l (Test species: n/a) (Toxicity not expected based on acute oral data) |

- **Specific symptoms in biological assay:** Not a classified acute dermal hazard.
- **Primary irritant effect:** Not a classified acute inhalative hazard.
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.

(Contd. on page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/06/2017

Reviewed on 06/06/2017

Trade name: EP1282 Black A

(Contd. of page 4)

- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

| | | | |
|-----------|--------------|--|----|
| 1333-86-4 | Carbon black | | 2B |
|-----------|--------------|--|----|

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

| | |
|---|--------------------------------|
| 25068-38-6 Bisphenol-A-(epichlorohydrin) epoxy resin | EC50 irritating mg/kg (rabbit) |
|---|--------------------------------|

| | |
|--|---|
| 74398-71-3 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid | EC50 slightly irri. mg/kg (Test species: n/a) Based on manufacturer's test result, the substance was slightly irritating to skin (Category 3). Reference: Hexion (M)SDS (2003). |
|--|---|

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/06/2017

Reviewed on 06/06/2017

Trade name: EP1282 Black A

(Contd. of page 5)

| | |
|--|--|
| · IMDG, IATA | III |
| · Environmental hazards: | Product contains environmentally hazardous substances: Bisphenol-A-(epichlorohydrin) epoxy resin |
| · Special precautions for user | Warning: Miscellaneous dangerous substances and articles |
| · Danger code (Kemler): | 90 |
| · EMS Number: | F-A,S-F |
| · Stowage Category | A |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation": | UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (BISPHENOL-A-(EPICHLOROHYDRIN) EPOXY RESIN), 9, III |

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **SARA Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **SARA Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **SARA Section 311/312 (Hazardous Chemical Inventory Reporting)**

| | | | |
|------------|--|------|--------|
| 25068-38-6 | Bisphenol-A-(epichlorohydrin) epoxy resin | A, C | 80-90% |
| 74398-71-3 | 1, 2, 3-Propanetriyl ester of 12-(oxiranylmethoxy)-9-octadecanoic acid | A, C | 10-20% |
| 1333-86-4 | Carbon black | A, C | 1-2.5% |

· **Hazard Abbreviations for SARA 311/312**

A - Acute Health Hazard
 C - Chronic Health Hazard
 F - Fire Hazard
 R - Reactive Hazard
 S - Sudden Release of Pressure Hazard

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

| | |
|-----------|---------------------------|
| 1333-86-4 | Carbon black |
| 106-89-8 | 1-chloro-2,3-epoxypropane |

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

| | |
|----------|---------------------------|
| 106-89-8 | 1-chloro-2,3-epoxypropane |
|----------|---------------------------|

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

| | | |
|-----------|--------------|----|
| 1333-86-4 | Carbon black | A4 |
|-----------|--------------|----|

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **International Regulation Lists**

· **Chinese Chemical Inventory of Existing Chemical Substances:**

All ingredients are listed.

· **GHS label elements** GHS label elements

· **National regulations:**

· **Japanese Existing and New Chemical Substance List:**

All ingredients are listed.

· **Korean Existing Chemical Inventory:**

All ingredients are listed.

· **European Pre-registered substances:**

All ingredients are listed.

(Contd. on page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/06/2017

Reviewed on 06/06/2017

Trade name: EP1282 Black A

(Contd. of page 6)

· **REACH - Substances of Very High Concern (SVHC) List:**

None of the ingredients is listed.

· **Restriction of Hazardous Substances Directive (RoHS) list:**

None of the ingredients is listed.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department Issuing (M)SDS:** Product Development Department
- **Contact:** msds@resinlab.com
- **Date of preparation / last revision** 06/06/2017 / 4 * **Data compared to the previous version altered.**

US